

Material Safety Data Sheet (91/155/EEC)

Date: 04.08.2005
Last Revised: 05.02.2003
Our Ref: 0163.1/LB (DR)

Page 1 of 2

1. Product and company information

Commercial product name: **SX Lead Flashing**

Supplier: Siroflex Ltd, Dodworth Business Park, Dodworth Barnsley S75 3SP, telephone: 01226 771600, facsimile: 01226 771601

Emergency phone: 01226 771600 (after working time) email to technical@siroflex.co.uk

2. Composition/information on ingredients

This product is a laminate of:-

- (i) A lacquered aluminum foil
- (ii) A self adhesive rubber modified bitumen compound
- (iii) A silicone coated release interleave

3. Hazard identification

This product is not especially hazardous to health but should be handled in accordance with good industrial hygiene and safety practices.

EYES: Practically non-irritating

SKIN: The foil has sharp edges, which can cut easily, otherwise product is practically non-toxic based on information available on the components.

INGESTION: Practically non-toxic based on the information available on the components.

4. First aid measures

Inhalation:

Normal use of product does not present a hazard.

Skin:

Wash skin thoroughly after use with soap and water, or use proprietary skin cleanser. Treat cuts with antiseptic plasters.

Eyes:

Remove by irrigating with copious amounts of water.

Ingestion:

Unlikely to occur.

5. Fire fighting measures

Fire Prevention:

This product is not flammable as such. However, it is possible to ignite it in a fire.

Suitable Extinguishing Media:

Water spray, foam, carbon dioxide or dry powder.

Unsuitable Extinguishing Media:

Special Exposure Hazards in Fires:

Combustion will produce dense smoke and toxic gases

Required Special Protective Equipment

For Fire Fighters:

Wear self-contained breathing apparatus, full protective clothing.

6. Accidental release measures

Precautions:

Collect up and place in a suitable container.

7. Handling and storage

Handling:

Store upright in original cartons in a cool dry place.

Storage:

Avoid over stacking of pallets.

Material Safety Data Sheet (91/155/EEC)

Product name: **SX Lead Flashing** Our Ref: 0163.1/LB (DR)

Page 2 of 2

8. Exposure controls and personal protection

Respiratory Protection: Not normally required

Hand Protection: The use of cotton or leather gloves and normal protective workwear is recommended.

Skin Protection: The use of proprietary barrier cream on the hands will aid removal of any product that might contaminate the hands. Observe normal standards of hygiene.

9. Physical and chemical properties

N/A

10. Stability and reactivity

Stable under normal conditions. Avoid acids, alkalis.

11. Toxicological information

Short term skin exposure may lead to dermatitis.

12. Ecological information

Mobility: Low

Degradability: Not readily biodegradable.

Bioaccumulation: No evidence to suggest bioaccumulation.

13. Disposal considerations

Products should always be disposed of in accordance with local regulations. It may be disposed of by either controlled incineration or a licensed waste disposal contractor.

14. Transport information

Not classified as hazardous for transport.

15. Regulatory information

Not classified.

16. Other information

The data contained in this Safety Data Sheet has been supplied as required by the **Chemical (Hazard Identification and Packaging) Regulations 1993**, as amended, for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided.

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, each user should review the recommendations in the specific context of the intended use and determine whether they are appropriate.
