

# Material Safety Data Sheet (91/155/EEC)

Date: 20.01.2011  
Replaces: 21.01.2010  
Our ref: 0175.5/LS(DR)

Page: 1/4

## 1. Product and company information

Commercial product name: SX Solvent Cleaner

Supplier: Siroflex Ltd, Dodworth Business Park, Dodworth Barnsley S75 3SP, telephone: 01226 771600, facsimile: 01226 771601

Emergency phone: 01226 771600 (after working time)

email to [technical@siroflex.co.uk](mailto:technical@siroflex.co.uk)

## 2. Hazard Identification

Main Hazard: Highly Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness or dizziness.

Other Hazards: In use, may form flammable/ explosive vapour-air mixture.

## 3. Composition/information on ingredients

<u>Hazardous substances</u>	<u>%</u>	<u>CAS</u>	<u>EINECS</u>	<u>Supply Class</u>
N-BUTYL ACETATE	10-30%	123-86-4	204-658-1	(-)R10 (Xi) R66 (-) R67
2-BUTOXYETHANOL	1-10%	111-76-2	203-905-0	(Xn) R20/21/22: (Xi) R36/38
ETHANOL	10-30%	64-17-5	200-578-6	(F) R11
LOW BOILING POINT HYDROGEN TREATED NAPHTHA – NAPHTHA (PETROLEUM), HYDRO TREATED LIGHT LOW BOILING POINT HYDROGEN TREATED NAPHTHA – NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY	30-50%	64742-49-0	265-151-9	(F+) R12 (Xi) R38 (N) R51/53 (Xn) R65
	1-10%	64742-82-1	265-185-4	(-) R10 (N) R51/53 (Xn) R65

## 4. First aid measures (Symptoms)

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Skin: There maybe irritation and redness at the site of contact.

Inhalation: There maybe irritation of the throat with a feeling of tightness in the chest.

Eyes: There maybe irritation and redness. The eyes may water profusely.

## 4. First aid measures (Action)

Ingestion: Wash out mouth with water. Do not induct vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Skin: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the effected skin with running water for 10 minutes or longer is substance is still on skin. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety while doing so. Consult a doctor.

Eyes: Bathe the eye with running water for 15 minutes. Consult a doctor

## 5. Fire fighting measures

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure Hazards: Highly Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

# Material Safety Data Sheet (91/155/EEC)

Product name: SX Solvent Cleaner

Our Ref: 0175.5/LS

Page: 2/4

## 6. Accidental Release Measures

### Personal Precautions:

Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### Environmental Precautions:

Do not discharge into drains or rivers. Contain the spillage using bunding.

### Clean-up Procedures:

Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

## 7. Handling and storage

### Handling Requirements:

Avoid contact with the substance. Ensure there is sufficient ventilation in the area. Do not handle in confined spaces. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### Storage Conditions:

Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up to electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

## 8. Exposure controls and personal protection

N-BUTYL ACETATE  
2-BUTOXYETHANOL  
ETHANOL

WEL (8hr exposure limit): 724mg/m<sup>3</sup>    WEL (15min exposure limit): 966mg/m<sup>3</sup>  
WEL (8hr exposure limit): 25ppm    WEL (15min exposure limit): 50ppm  
WEL (8hr exposure limit): 1920mg/m<sup>3</sup>

### Engineering Measures:

Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

### Respiratory Protection:

Self-contained breathing apparatus must be available in case of emergency.

### Hand Protection:

Impermeable gloves.

### Eye Protection:

Safety glasses. Ensure eye bath is to hand.

### Skin Protection:

Impermeable protective clothing.

## 9. Physical and chemical properties

State: Liquid  
Colour: Colourless  
Odour: Perceptible odour  
Solubility in water: Highly soluble  
Also soluble in: Methanol. Acetone  
Boiling point/ range °C: 78.4-115.4  
Melting point/ range °C: 0  
Flammability limits %: lower: 3.3  
: upper: 19.0  
Flash point °C: 12  
Autoflammability °C: 230  
Vapour pressure: 5.8 kPa  
Relative density: 0.791

## 10. Stability and reactivity

### Stability:

Stable under normal conditions. Stable at room temperature.

### Hazardous decomposition products:

In combustion emits toxic fumes. Oxides of carbon.

### Materials to avoid:

Strong oxidising agents. Strong acids.

### Conditions to avoid:

Heat. Hot surfaces. Sources of ignition. Flames.

# Material Safety Data Sheet (91/155/EEC)

Product name: SX Solvent Cleaner

Our Ref: 0175.5/LS

Page: 3/4

## 11. Toxicological information

<u>Hazardous Ingredients:</u>	N-BUTYL ACETATE	ORL MUS LD50 6gm/kg ORL RAT LD50 10768 mg/kg
	2-BUTOXYETHANOL	IVN RAT LD50 307 mg/kg ORL MUS LD50 1230 mg/kg ORL RAT LD50 470 mg/kg
	ETHANOL	IVN RAT LD50 1440 mg/kg ORL MUS LD50 3450 mg/kg ORL RAT LD50 7060 mg/kg

Routes of Exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. Ecological information

<u>Mobility:</u>	Readily absorbed into soil.
<u>Persistence &amp; Degradability:</u>	Biodegradable.
<u>Bio-Accumulation:</u>	No bioaccumulation potential.
<u>Other adverse effects:</u>	Negligible ecotoxicity.

## 13. Disposal considerations

**NB:** The users attention is drawn to the possible existence of regional or national regulations regarding disposal.

## 14. Transport information

### ADR/ RID

<u>UN No. :</u>	1993
<u>Packing Group:</u>	II
<u>Shipping Name:</u>	FLAMMABLE LIQUID N.O.S. (LOW BOILING POINT HYDROGEN TREATED NAPHTHA – N-BUTYL ACETATE.)
<u>Labelling:</u>	3
<u>ADR Class:</u>	3
<u>Classification Code:</u>	F1
<u>Hazard Identity Number:</u>	33

### IMDG/ IMO

<u>UN No. :</u>	1993
<u>Packing Group:</u>	II
<u>Marine Pollutant:</u>	
<u>Class:</u>	3
<u>EMS:</u>	F-E, S-E*
<u>Labelling:</u>	3

### IATA/ ICAO

<u>UN No. :</u>	1993
<u>Packing Group:</u>	II
<u>Labelling:</u>	3
<u>Class:</u>	3
<u>Packing Instructions:</u>	305 (P&CA): 307(CAO)

# Material Safety Data Sheet (91/155/EEC)

Product name: SX Solvent Cleaner

Our Ref: 0175.5/LS

Page: 4/4

## 15. Regulatory information

Hazard Symbols:

**HIGHLY FLAMMABLE**  
**DANGEROUS FOR THE ENVIRONMENT**  
**HARMFUL**

Risk Phrases:

R11 Highly Flammable  
R38 Irritating to skin  
R51/ 53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment  
R65 Harmful: may cause lung damage if swallowed  
R66 Repeated exposure may cause skin dryness or cracking  
R67 Vapours may cause drowsiness and dizziness

Safety Phrases:

S16 Keep away from sources of ignition – No smoking  
S33 Take precautionary measures against static discharges  
S43 In case of fire, use dry chemical powder  
S61 Avoid release to the environment. Refer to special instructions/ safety data sheets.  
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show the container or label

Note:

The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The users attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. Other information

Risk Phrases used in s2R10

Flammable  
R66 Repeated exposure may cause skin dryness or cracking  
R67 Vapours may cause drowsiness or dizziness  
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed  
R36/ 38 Irritating to eyes and skin  
R11 Highly flammable  
R12 Extremely flammable  
R38 Irritating to skin  
R51/ 53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment  
R65 Harmful: may cause lung damage if swallowed

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, each user should review the recommendations in the specific context of the intended use and determine whether they are appropriate.