

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *SX Contractors Hand Held Foam*
- **Article number:** 8404
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** *Sealant*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SIROFLEX LIMITED
Dodworth Business Park, Dodworth,
Barnsley, South Yorkshire, S75 3SP
-
- Tel: 01226 771600 Fax: 01226 771601*
- **Further information obtainable from:**
www.siroflex.co.uk
info@siroflex.co.uk
- **Emergency telephone number:** *Tel: +49 (0)9366/9071-26 Monday to Thursday 7:15 to 18:00 CET*

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335 May cause respiratory irritation.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Lact. H362 May cause harm to breast-fed children.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20-40-48/20: Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.



Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: **SX Contractors Hand Held Foam**

(Contd. of page 1)

**F+**; Extremely flammable**R12:** Extremely flammable.**R53-64:** May cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies.**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xn Harmful

F+ Extremely flammable

Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues

Risk phrases:

12 Extremely flammable.

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

40 Limited evidence of a carcinogenic effect.

42/43 May cause sensitisation by inhalation and skin contact.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

53 May cause long-term adverse effects in the aquatic environment.

64 May cause harm to breastfed babies.

Safety phrases:

16 Keep away from sources of ignition - No smoking.

23 Do not breathe fumes/aerosol.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of soap and water.

37/39 Wear suitable gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

51 Use only in well-ventilated areas.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

Classification in accordance with Directive 75/324/EEC: Extremely flammable**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: **SX Contractors Hand Held Foam**




















(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues  Xn R20-40-48/20;  Xn R42/43;  Xi R36/37/38  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;  Acute Tox. 4, H332; STOT SE 3, H335; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 85535-85-9 EINECS: 287-477-0	alkanes, C14-17, chloro  N R50/53 R64  Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	10-25%
CAS: 75-28-5 EINECS: 200-857-2	isobutane  F+ R12  Flam. Gas 1, H220;  Press. Gas, H280	2.5-10%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether  F+ R12  Flam. Gas 1, H220;  Press. Gas, H280	2.5-10%
CAS: 74-98-6 EINECS: 200-827-9	propane  F+ R12  Flam. Gas 1, H220;  Press. Gas, H280	2.5-10%
CAS: 106-97-8 EINECS: 203-448-7	butane  F+ R12  Flam. Gas 1, H220;  Press. Gas, H280	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Take affected persons into fresh air and keep quiet.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
Immediately remove any clothing soiled by the product.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Water spray
Foam
Fire-extinguishing powder

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: SX Contractors Hand Held Foam

(Contd. of page 3)

- Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- Nitrogen oxides (NOx)
- Hydrogen chloride (HCl)
- Hydrogen cyanide (HCN)
- Carbon monoxide and carbon dioxide
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections** See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: SX Contractors Hand Held Foam

(Contd. of page 4)

· **Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

· **Additional information:** The lists valid during the making were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Recommended filter device for short term use:** Filter AX· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm· **Penetration time of glove material** ≥ 60 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Aerosol**Colour:** Various colours

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: SX Contractors Hand Held Foam

(Contd. of page 5)

· Odour:	Product specific
· Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: Not applicable, as aerosol.	
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	>200°C
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Density at 20°C:	0.98731 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Organic solvents:	17.4 %

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with alkali, amines and strong acids.
- **Hazardous decomposition products:**
Hydrogen chloride (HCl)
Hydrogen cyanide (prussic acid)
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	0.49 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Vapours have narcotic effect.
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.
- **Sensitisation** May cause sensitisation by inhalation and skin contact.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: **SX Contractors Hand Held Foam**

(Contd. of page 6)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

16 05 04	gases in pressure containers (including halons) containing dangerous substances
08 05 01	waste isocyanates
15 01 10	packaging containing residues of or contaminated by dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **UN proper shipping name:** 1950 AEROSOLS
- **Limited quantities (LQ)** LQ2
- **Transport category** 2
- **Tunnel restriction code** D

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 03.03.2011

Replaces: 25.02.2010

Ref: 0045.9.A/DR

Trade name: **SX Contractors Hand Held Foam**

(Contd. of page 7)

· **Proper shipping name:** AEROSOLS· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 2.1
 · **UN/ID Number:** 1950
 · **Label:** 2.1
 · **Packaging group:** -
 · **Proper shipping name:** AEROSOLS, flammable

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1
 · **Special precautions for user Warning:** Gases.

15 Regulatory information

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H362 May cause harm to breast-fed children.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

R12 Extremely flammable.
 R20 Harmful by inhalation.
 R36/37/38 Irritating to eyes, respiratory system and skin.
 R40 Limited evidence of a carcinogenic effect.
 R42/43 May cause sensitisation by inhalation and skin contact.
 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R64 May cause harm to breastfed babies.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered.**