

TECHNICAL DATA SHEET

SX SCREWS

PRODUCT DESCRIPTION: Zinc plated high quality hardened chipboard screws, pozi drive, for general fixing.

COLOUR: Brass

PACKAGING: 4mm x 25mm, 4mm x 30mm, 4mm x 40mm, 4mm x 45mm
4mm x 50mm, 4mm x 60mm, 4mm x 70mm
5mm x 25mm, 5mm x 40mm, 5mm x 45mm,
5mm x 50mm, 5mm x 60mm, 5mm x 70mm,
5mm x 80mm, 5mm x 90mm, 5mm x 100mm
Packed 100 to each box.
Minimum order 10 boxes per size.

FINISHING

It is the user's responsibility to dispose of all packaging correctly.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

TECHNICAL DATA	SX SCREWS
Grade of steel	SAE1022A
Tensile stress of steel	U470 N/mm ²
Hardness of steel	U150 HV

For information on other Siroflex products please contact our technical department by telephone or email to technical@siroflex.co.uk

Issue 3/ 10.11.2010

Page 1 of 1

DODWORTH BUSINESS PARK
DODWORTH BARNSELY
SOUTH YORKSHIRE S75 3SP

TELEPHONE: 01226 771600
FACSIMILE: 01226 771601
e-mail info@siroflex.co.uk
www.siroflex.co.uk

Registered in England No. 2831699
Member of the Den Braven Sealant Group of Companies