

# TECHNICAL DATA SHEET

## SX SILICONE SPRAY

A multipurpose silicone spray that provides a thin, durable, clear, odourless film that lubricates, protects and eliminates squeaking and binding caused by friction and is an excellent mould release.

### USES

Lubricating, waterproofing and to protect rubber, plastic, pvc, metal, nylon and wood. Restoring, protecting and preserving rubber mats, mountings and seals, vinyl tops, weather stripping, dashboards etc. Protecting and lubricating tools, locks, zips, switches etc. Mould release for plastics and composites. This product has approval for use as a lubricant on hot and cold plastic pipes to BS6920.

**PACKAGING:** 400ml aerosol packed 1 x 12

### PREPARATION

Surfaces must be clean dry and grease free. Shake the can vigorously.

### APPLICATION

Hold can upright, approximately 20cm from the surface. Spray lightly over the surface to achieve the required level of finish. Rub with a soft cloth and repeat this operation as required. Do not spray directly onto hot surfaces.

### FINISHING

Remove any excess silicone spray with a dry cloth and wash area with plenty of soapy water. It is the user's responsibility to dispose of all packaging correctly.

## **SX SILICONE SPRAY TECHNICAL DATA SHEET CONTINUED**

### **HEALTH & SAFETY**

#### **EXTREMELY FLAMMABLE**

Contains Aliphatic Hydrocarbon.

Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Keep container in a well-ventilated place. Keep away from sources of ignition. Use only in well-ventilated areas. This material and its container must be disposed of as hazardous waste.

### **STORAGE**

Store upright in well ventilated areas only. Storage temperature should never exceed 50°C. Shelf Life 12 months.

### **LIABILITY**

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.