

Safety Data Sheet
according to 1907/2006/EC, Article 31

Date: 30.07.2009

Replaces: 06.08.2008

Ref: 0006.6.A/DR

Page 1 of 6

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** TECTANE Adhesive Spray
- **Article number:** 4700004
- **Application of the substance / the preparation** Adhesives
- **Manufacturer/Supplier:**
Siroflex Limited
Dodworth Business Park, Dodworth,
Barnsley, South Yorkshire, England, S75 3SP
Tel.: 01226 771600
Fax.: 01226 771601
info@siroflex.co.uk
- **Further information obtainable from:**
www.siroflex.co.uk

2 Hazards identification

- **Hazard description:**



Xi Irritant
F+ Extremely flammable
N Dangerous for the environment

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Harmful: may cause lung damage if swallowed.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether F+; R 12	25-50%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn, Xi, F, N; R 11-38-51/53-65-67	25-50%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 2)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Date: 30.07.2009

Replaces: 06.08.2008

Ref: 0006.6.A/DR

Page 2 of 6

Trade name: TECTANE Adhesive Spray

(Contd. of page 1)

4 First aid measures

- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Take affected persons into fresh air and keep quiet.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards caused by the substance, its products of combustion or resulting gases:**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Additional information:** See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.

(Contd. on page 3)

GB

Safety Data Sheet
according to 1907/2006/EC, Article 31

Date: 30.07.2009

Replaces: 06.08.2008

Ref: 0006.6.A/DR

Page 3 of 6

Trade name: TECTANE Adhesive Spray

(Contd. of page 2)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Recommended filter device for short term use:** Filter AX
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.45 mm
- **Penetration time of glove material**
 ≥ 240 min
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **General Information**

Form:	Aerosol
Colour:	Whitish
Odour:	Petrol-like

- **Change in condition**
Melting point/Melting range: Undetermined.

(Contd. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Date: 30.07.2009

Replaces: 06.08.2008

Ref: 0006.6.A/DR

Page 4 of 6

Trade name: TECTANE Adhesive Spray

(Contd. of page 3)

Boiling point/Boiling range:	< 0°C
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	>200°C
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Density at 20°C:	0.72596 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Organic solvents:	82.2 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:**
Aldehyde
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rab)
Inhalative	LC50/4 h	>5 mg/l (rat)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Vapours have narcotic effect.

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

GB

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Date: 30.07.2009

Replaces: 06.08.2008

Ref: 0006.6.A/DR

Page 5 of 6

Trade name: TECTANE Adhesive Spray

(Contd. of page 4)

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

16 05 04	gases in pressure containers (including halons) containing dangerous substances
----------	---

15 01 04	metallic packaging
----------	--------------------

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 2 5F Gases.

· **Danger code (Kemler):** 23

· **UN-Number:** 1950

· **Packaging group:** -

· **Hazard label:** 2.1

· **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



· **IMDG Class:** 2.1

· **UN Number:** 1950

· **Label:** 2.1

· **Packaging group:** -

· **EMS Number:** F-D,S-U

· **Marine pollutant:** No

· **Proper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 2.1

· **UN/ID Number:** 1950

· **Label:** 2.1

· **Packaging group:** -

· **Proper shipping name:** AEROSOLS, flammable

GB

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Date: 30.07.2009

Replaces: 06.08.2008

Ref: 0006.6.A/DR

Page 6 of 6

Trade name: TECTANE Adhesive Spray

(Contd. of page 5)

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xi Irritant

F+ Extremely flammable

N Dangerous for the environment

· **Risk phrases:**

12 Extremely flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

23 Do not breathe aerosol.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

11 Highly flammable.

12 Extremely flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.