

TECHNICAL DATA SHEET

TECTANE CAVITY PROTECTION SPRAY 1 LITRE

Cavity Protection Spray prevents and stops rust from within. Its excellent flow properties enable it to penetrate into the smallest of spaces.

USES

Cavity Protection Wax can be applied in cars and other vehicles for all cavities of the body, such as doors, sides, insides, bonnets, deck lids, cross-ties, body reinforcements, headlamp casings, etc.

Other characteristics are:

- Protects all round
- Has a brownish colour
- Forms a sticking and water repellent film
- Dries fast
- Good adhesion

Cavity Protection Wax is also suitable for:

- The wintering of equipment in the building and construction trade as well as in the agricultural business
- The sealing of joints, grooves and welds

PACKAGING: 1 Litre

PREPARATION

Take off coverings which are easy to dismantle, such as on doors. All surfaces must be clean, dry and free from oil, grease or any contamination. Shake can well before use.

APPLICATION

Apply a thin layer using a gun preferably at a pressure of 6 bar and with the material at a temperature of more than 15°C.

HEALTH & SAFETY

Flammable. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from sources of ignition - no smoking. Do not breathe fumes/ aerosol. If swallowed seek medical advice and show this container or label. Use only in well-ventilated areas. Dispose of this material and its container to hazardous or special waste collection point.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

Full health and safety data information can be downloaded from www.siroflex.co.uk

Issue5/ 0029.6.A/30.09.2009/DR