

Safety data sheet

according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** *Tectane PTFE-Spray*
- **Article number:** 6020001-6020099
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** *Lubricant*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SIROFLEX LIMITED
Dodworth Business Park, Dodworth,
Barnsley, South Yorkshire, S75 3SP
-
- Tel: 01226 771600*
Fax: 01226 771601
- **Further information obtainable from:**
www.siroflex.co.uk
info@siroflex.co.uk
-
- **Emergency telephone number:** *Tel: +49 (0)9366/9071-26 Monday to Thursday 7:15 to 18:00 CET*

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

R52/53-66-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Harmful: may cause lung damage if swallowed.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

Trade name: Tectane PTFE-Spray

(Contd. of page 1)

Code letter and hazard designation of product:

F+ Extremely flammable

Risk phrases:

- 12 Extremely flammable.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe spray.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

Special labelling of certain preparations:

- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
- Do not spray on a naked flame or any incandescent material.
- Buildup of explosive mixtures possible without sufficient ventilation.
- Keep out of the reach of children

Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 75-28-5 EINECS: 200-857-2	isobutane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 74-98-6 EINECS: 200-827-9	propane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	25-50%
CAS: 64742-49-0 EINECS: 265-151-9 Reg.nr.: 01-2119475514-35-xxxx	Naphtha (petroleum), hydrotreated light Xn R65; Xi R38; F R11; N R51/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 106-97-8 EINECS: 203-448-7	butane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	2.5-10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

Trade name: **Tectane PTFE-Spray**

(Contd. of page 2)

4 First aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Take affected persons into fresh air and keep quiet.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections** See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

Trade name: Tectane PTFE-Spray

(Contd. of page 3)

*Protect against electrostatic charges.**Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.*· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:***Store in a cool location.**Observe official regulations on storing packagings with pressurized containers.*· **Information about storage in one common storage facility:** *Not required.*· **Further information about storage conditions:** *Protect from heat and direct sunlight.*

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** *No further data; see item 7.*· **Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****106-97-8 butane**

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

· **Additional information:** *The lists valid during the making were used as basis.*· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:***Keep away from foodstuffs, beverages and feed.**Immediately remove all soiled and contaminated clothing**Wash hands before breaks and at the end of work.**Do not inhale gases / fumes / aerosols.**Avoid contact with the eyes and skin.*· **Respiratory protection:***In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.**Use suitable respiratory protective device in case of insufficient ventilation.*· **Recommended filter device for short term use:** *Filter AX*· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.· **Material of gloves***Nitrile rubber, NBR**Recommended thickness of the material: ≥ 0.45 mm*· **Penetration time of glove material***≥240 min**The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*· **Eye protection:**

Tightly sealed goggles

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

Trade name: *Tectane PTFE-Spray*

(Contd. of page 4)

· **Body protection:** *Protective work clothing*

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**· **Form:** *Aerosol*· **Colour:** *Whitish*· **Odour:** *Petrol-like*· **Change in condition**· **Melting point/Melting range:** *Undetermined.*· **Boiling point/Boiling range:** *Undetermined.*· **Flash point:** *Not applicable, as aerosol.*· **Ignition temperature:** *>200°C*· **Danger of explosion:** *Product is not explosive. However, formation of explosive air/vapour mixtures are possible.*· **Density at 20°C:** *0.60191 g/cm³*· **Solubility in / Miscibility with**· **water:** *Not miscible or difficult to mix.*· **Organic solvents:** *92.5 %*

10 Stability and reactivity

· **Reactivity**· **Chemical stability**· **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*· **Possibility of hazardous reactions** *No dangerous reactions known.*· **Hazardous decomposition products:***Aldehyde**Carbon monoxide and carbon dioxide*

11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values relevant for classification:****64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rab)

Inhalative LC50/4 h >5 mg/l (rat)

· **Primary irritant effect:**· **on the skin:** *Irritant to skin and mucous membranes.*· **on the eye:** *No irritating effect.*· **Sensitization:** *No sensitizing effects known.*· **Additional toxicological information:** *Vapours have narcotic effect.*

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

Trade name: Tectane PTFE-Spray

(Contd. of page 5)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** 23
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **UN proper shipping name:** 1950 AEROSOLS
- **Limited quantities (LQ)** LQ2
- **Transport category** 2
- **Tunnel restriction code** B1D

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Date: 22.09.2011

Replaces: 30.09.2010

Ref: 0166.6.A/DR

Trade name: Tectane PTFE-Spray

(Contd. of page 6)

· **Proper shipping name:** AEROSOLS· **Air transport ICAO-TI and IATA-DGR:**· **ICAO/IATA Class:** 2.1· **UN/ID Number:** 1950· **Label:** 2.1· **Packaging group:** -· **Proper shipping name:** AEROSOLS, flammable· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1· **Special precautions for user Warning:** Gases.

15 Regulatory information

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered.**