

TECHNICAL DATA SHEET

TECTANE PAINT AND GASKET STRIPPER

Paint and Gasket Stripper can be applied everywhere where sticking adhesive, sealant, packaging or lacquer residues have to be removed in a rapid and effortless way. With Paint and Gasket Stripper, the use of mechanical remedies are unnecessary.

USES

Paint and Gasket Stripper can be applied on metal, wood, glass, ceramics, polyethylene and polypropylene.

Paint and Gasket Stripper is a strong, thixotropic mixture of active substances. Its particularly strong solving effect makes the application extremely easy (even on vertical surfaces).

The product is mainly used in industry, garages and other trades where sticking residues have to be removed in a rapid and gentle way.

- dissolves even the most stubborn adhesive residues, such as anaerobic products and adhesive made of cyanacrylic resin.
- Removes without effort paints, lacquers, oils, resins as well as oil carbon, tar, grease and lubricant residues.

PACKAGING: 400ml aerosol

APPLICATION

Shake the aerosol vigorously before use. Spray the surface needing treatment from a distance of approx. 25cm. After applying the product, let it work into the surface for about 5 to 10 minutes. The partially dissolved residues are then carefully removed with the help of a scraper.

HEALTH & SAFETY

EXTREMELY FLAMMABLE IRRITANT

Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Do not breathe aerosol. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed seek medical advice and show this container or label. Use only in well ventilated areas. Dispose of this material and its container to hazardous or special waste collection point. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children.

TECTANE PAINT AND GASKET STRIPPER TECHNICAL DATA SHEET CONTINUED

LIMITATIONS

It is not recommendable to apply Tectane Paint and Gasket Stripper on sensitive plastics, such as PVC, synthetics or linoleum. Test plastic compatibility before use.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

Full health and safety data information can be downloaded from www.siroflex.co.uk.