

TECHNICAL DATA SHEET

TECTANE PROTECTION WAX

Protection Wax is an ideal protection from rust in grooves and on surfaces. It offers long-lasting protection from corrosion, oxidation and dirt. After the wax has dried up, there remains a sticky, plasticine-like, water-repellent film which is almost colourless. Saltwater and heat-resistant (100°C).

USES

Its excellent flow properties make Protection Wax also suitable for inaccessible areas. Protection Wax is used for preserving grooves, surfaces and cavities in motor vehicles, building machinery, agricultural implements as well as for gadgets employed in household and garden. Its light colour makes it particularly suitable for the protection of grooves in car bonnets and boots.

Protection Wax is suitable for both a secondary treatment, such as after an accident, and a first treatment.

It is also a preferred means of preserving an engine compartment that has just been cleaned.

PACKAGING: 400ml aerosol packed 1 x 12

PREPARATION

Before use, pre-treat Protection Wax, if necessary, with a cleaner, primer or Zinc-Aluminium Spray.

APPLICATION

Spray the wax on in a thin layer and let it dry. Plastic and rubber are not affected.

HEALTH & SAFETY

EXTREMELY FLAMMABLE

DANGEROUS FOR THE ENVIRONMENT

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause drowsiness and dizziness. Do not breathe aerosol. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

For full health and safety data information, please contact our technical department by telephone or email to technical@siroflex.co.uk

Issue7/ 002.8.A/07.07.2011DR