

TECHNICAL DATA

TECTANE RUST PRIMER RED

Rustprimer Red stops corrosion on ferrous metals, serves as an all-purpose adhesive agent for lacquers and can be applied on rust that has become firmly stuck. Rustprimer Red consists of a combination of anti-rust pigments and binders. That is why it not only protects shiny material from rust, but also protects rusty surfaces from additional rust formation.

USES:

The special advantages of Rustprimer Red are:

- a smooth, non-porous and particularly non-abrasive protective layer
- can be lacquered over with a great number of coating materials
- corrosion-resistant
- resistant to water, salt water, petrol and most aggressive chemicals
- in dry heat, temperature-resistant up to +140°C (short period)
- lead-free, non-toxic and acid-free

Motor vehicle factories: coating and repairing of body parts, cross-ties, cavities, coachwork, trailers, surface mountings, etc.

Building and construction industry and public enterprises: building machinery, mining, bridge construction, railways, electric power stations, gas works, railing construction, road construction as well as big machinery.

Industrial enterprises of all sorts: tank construction, ferrous metals, garage doors, horticulture, canteen kitchens and large laundries, air-conditioning, steel-girder construction, structural steel work, fuel storage depots, frames, etc.

PACKAGING: 400ml aerosol

PREPARATION

Ideal temperature 16°C – 25°C. The surfaces to be coated must be dry as well as free of fat, oil, dust and rust. Shake the aerosol vigorously for approx. 3 minutes (after the clearly audible striking of the metal balls).

APPLICATION

Apply it crosswise from a distance of approx. 25-30cm. The surface will be dust dry after approx. 15 minutes (20°C) and fast to handling after approx. ten more minutes.

FINISHING

The product will be completely dry after approx. 24 hours. After that, it can be lacquered over with various lacquers and paints (do your own testing!)

HEALTH & SAFETY

EXTREMELY FLAMMABLE IRRITANT

Extremely flammable. Irritating to skin. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Do not breathe aerosol. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed seek medical advice immediately and show this container or label. Use only in well ventilated areas. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

Full health and safety data information can be downloaded from www.siroflex.co.uk.

Issue4/ 0020.8.A/19.12.2011/DR