

# TECHNICAL DATA SHEET

## *TECTANE SILVER WHEEL SPRAY*

Silver Wheel Spray makes wheel rims, chrome and moulding weather- and salt-resistant and protects them from corrosion and rust. It also gives a sporty metal gleam to the wheel rims.

### **USES**

Silver Wheel Spray is based on synthetic resin, possesses a high scuff resistance, is robust and offers the rim (and other silver-coloured objects) lasting protection from stone chipping, de-icing salt and similar negative influences. Its excellent flow properties allow Silver Wheel Spray to protect even inaccessible areas and joints.

- adheres to metal, wood, new and old paintwork
- is economic
- dries fast
- does not run off

**PACKAGING:** 400ml

### **PREPARATION**

Ideal temperature: 16°C –25°C. Take off the wheel and remove the hub cap. Clean rust and dirt carefully from the rim. Cover the tyre. Shake the spray vigorously for about two minutes after the clearly audible striking of the metal ball.

### **APPLICATION**

Spray the surface to be treated crosswise from a distance of 25 to 30cm. Silver Wheel Spray is dust dry after no more than approx. 10 minutes.

### **HEALTH & SAFETY**

#### **EXTREMELY FLAMMABLE IRRITANT**

Extremely flammable. Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed seek medical advice immediately and show this container or label. Use only in well ventilated areas. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children.

### **LIABILITY**

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

Full health and safety data information can be downloaded from [www.siroflex.co.uk](http://www.siroflex.co.uk)