

TECHNICAL DATA SHEET

TECTANE WHITE GREASE

Tectane White Grease can be applied as grease lubrication on highly-stressed bearings, spindles and guides in machines. However, it can also be applied as a long-lasting lubricant. It prolongs the intervals after which lubrication becomes necessary owing to its double lubricating effect. White Grease ensures a longer functioning of expensive installations with fewer failures and repairs.

USES

Tectane White Grease creates long-lasting lubrication and protection.

- long-term resistant to salt water
- temperature resistant from -30°C up to +120°C (only for a short period of time)
- highly effective due to its perfectly combined double lubricating effect
- prevents rust formation
- adheres extremely well
- saves the costs of maintenance and lubricants by reducing the number of failures and repairs

Tectane White Grease is suitable for lubricating highly-stressed slide, roller and swing bearings as well as spindles and guides in machines used in industry, vehicle construction and shipbuilding as well as in operating building and agricultural machinery.

- lubricates moveable parts and sliding surfaces
- suitable as a back-up lubricating grease on spotless lubricating points
- reduces the wear and tear on bearings, shafts, chains, chain wheels, brake hinges and locks.
- also suitable as a battery pole grease, a parting agent and preservative

PACKAGING: 400ml aerosol

PREPARATION

Thoroughly clean the lubricating points (e.g. with Brake Cleaner) and remove old grease residues. Shake the aerosol vigorously (for about 2 minutes) before use till the metal ball can be heard clearly.

APPLICATION

Spray Tectane White Grease sparingly and evenly from a distance of approx. 20cm. After use, turn the aerosol up and empty it by spraying its contents till there is only propellant left.

TECTANE WHITE GREASE TECHNICAL DATA SHEET CONTINUED

HEALTH & SAFETY

EXTREMELY FLAMMABLE IRRITANT DANGEROUS FOR THE ENVIRONMENT

Irritating to skin. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness. Do not breathe aerosol. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated area. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.