

TECHNICAL DATA SHEET

TECTANE ZINC SPRAY

Zinc Spray is a fast-drying protection from corrosion with excellent long-term effect for metals. In dry film, Zinc Spray contains more than 90% zinc and zinc-compounds.

USES

Adheres to almost all metals, has a smooth and penetrating film. Can be used in spot-welding and is heat-resistant up to 500°C. Can be lacquered over.

Zinc Spray can be used

- in repairing damaged zinc layers
- in coating drilling, cutting and welding points
- as a conducting intermediate layer in spot-welding
- as a primary coat for installations at risk from water and weather effects
- with all bodywork
- everywhere where metal must be protected from corrosion

Zinc Spray can be applied in all sectors of industry and trade as well as in body manufacturing, particularly in areas where metals are exposed to corrosion.

- DIN 53167 salt spray test in combination with DIN 50021: 400 hours/80 my < 0,5 mm
- DIN 53151 cross-cut test: Gt 0-1.

PACKAGING: 400 ml

PREPARATION

Ideal temperature 16°C – 25°C. Degrease metals and grind them smoothly. Shake the spray vigorously for about three minutes after the clearly audible striking of the metal ball.

APPLICATION

Apply the spray crosswise from a distance of approx. 25-30cm. The surface is dry after 5-7 minutes, fast to handling after 20-30 minutes and completely dry after approx. 24 hours.

HEALTH & SAFETY

EXTREMELY FLAMMABLE

DANGEROUS FOR THE ENVIRONMENT

Extremely flammable. Very toxic to aquatic organisms, may cause long-term damage in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Keep out of the reach of children. Do not breathe aerosol. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed seek medical advice immediately and show this container or label. Use only in well ventilated areas. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Keep away from sources of ignition – No smoking. Build-up of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However, as Siroflex Limited cannot know all the uses its products may be put to, and as application methods are out of our control it is the users responsibility to determine suitability of use.

Full health and safety data information can be downloaded from www.siroflex.co.uk.