



Technical Data Sheet

Zwaluw B&B Primer Universal

Adhesion promotor for butyl and bituminious membranes



Product Description

Zwaluw B&B Primer Universal is a very quick-drying transparent primer for porous surfaces such as stone, concrete and wood. Zwaluw B&B Primer Universal was developed and tailored to the butyl and bituminous based Den Braven membranes, such as Zwaluw Butylband, Zwaluw Butylband Fleece and Zwaluw Alu- & Loodband. The drying time of the Zwaluw B&B Primer Universal is fast in order to maintain efficiency.

Benefits

- Fast Drying
- Ideal in combination with Zwaluw membranes

Applications

Zwaluw B&B Primer Universal was developed to secure optimum adhesion and to prevent moisture intrusion from the construction. For the application with the butyl and bituminous membranes of Zwaluw.

Directions Of Use

For a complete overview see our website or contact Den Braven.

Additional information

Application temperature	0°C to +30°C
Flash point	-4°C
Frost resistance during transportation	Up to -15°C

These are typical values

Limitations

Surface Preparations and Finishing

Before using the Zwaluw B&B Primer Universal refer to the Health & Safety Sheet. All surfaces must be clean, dry and free of dust, grease and other loose material. Thoroughly clean by using a Zwaluw Cleaner and two cloths. Contact our Centre of Excellence for a full recommendation. Clean brush immediately with Zwaluw Cleaner. Clean hands with Zwaluw Wipes. Apply Zwaluw B&B Primer Universal with a paint brush. Apply a thin and even film.

Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

Colour(s)

Transparent

Packaging

• Can

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life up to 12 months from production date, stored in a dry place.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the product sprior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

