



Technical Data Sheet

Zwaluw PUR Remover Cured PU foam remover



Product Description

Zwaluw PUR Remover is a ready to use paste to remove residues of cured PUR foam from glass, aluminium, PVC, laminate floors, formica and ceramic tiles.

Benefits

· Removes hardened PU foam

Applications

Zwaluw PUR Remover has been developed to remove cured PU foam

Directions Of Use

Using a sharp knife, cafefully cut the PU foam away as much as possible. Apply Den Braven® QEC003C excessively over the cured PUR foam residue. After 30-120 minutes the softened PU foam sealant should be removed with a plastic or a wooden spatula. Resultant slurry should be wiped off with a dry cloth. If necessary repeat the treatment. When all the PU foam is removed, clean the substrate with a wet cloth. Left over PUR Remover should not remain on the surfaces longer than necessary! Den Braven® QEC003C is hygroscopic, (sensitive to moisture) so close container immediately after use. Only undiluted product maintains its strength.

Additional information

Application temperature	+5°C to +30°C
Consistency	Paste
Density	1,54 g/ml
Frost resistance during transportation	Up to -15°C

These are typical values

Limitations

 If using on plastic, test in an unseen place for tolerance to solvent (especially in case of materials of unknown origin)

Surface Preparations and Finishing

Cleaning

Colour(s)

• White

Packaging

Bottle

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 24 months after production date, stored in a dry place.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

