

Technical Data Sheet

Zwaluw Super Adhesive Fast super glue



Product Description

Zwaluw Super Adhesive is a liquid, fast curing adhesive based on cyanoacrylic. The adhesive cures through contact with moisture.

Benefits

- Cures in seconds
- · For bonding rubber, glass, metal and plastic

Applications

Zwaluw Super Adhesive was developed for bonding among others rubber rings, glass, metals and plastics at for example modelling, jewellery and ornaments. Also for bonding rubber profiles in glazing systems.

Directions Of Use

The surfaces to be glued must fit together well. Apply glue to one side, straight from the plastic bottle and hold the parts together while applying pressure for 5 seconds. For best bonding the adhesive layer must be thin. Do not apply the adhesive in excessive quantities. Take care that the adhesive does not come in contact with the eyes or skin. Always test adhesion prior to application.

Additional information

Application temperature	+5°C to +30°C
Base	Cyano-acrylic
Curing time	3-30 seconds
Density	1,05 g/ml
Open time	0-3 seconds
Tensile strength	10 N/mm²
Viscosity	120 mPas

These are typical values

Limitations

• Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Application temperature: +5°C to +30°C (applies to environment and substrates). All substrates must be smooth, clean, dry, and free of dust, oil and grease. Before using the Zwaluw Super Adhesive refer to the Health & Safety Sheet.

Cleaning

After skin contact immediately wash with lukewarm water and soap and rinse thoroughly.

Colour(s)

Transparent

Packaging

Flacon

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 12 months after date of production, stored in a dry place.

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites.





Technical Data Sheet

Zwaluw Super Adhesive

Fast super glue

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik's written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document. Bostik cannot be hed liable for any damage, either directly or indirectly, due to the use of the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be hed liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

