



Technical Data Sheet

Shell Tixophalte Wet

Bituminous adhesive and sealant



Product Description

Tixophalte Wet is a professional bituminous adhesive and sealant with permanent flexibility giving superior adhesion. Tixophalte Wet is a plasto-elastic, neutral hardening mastic. It is based on a (thixotropic) high-quality modified bitumen/rubber composition and contains additives, fillers and a non-toxic and non-flammable solvents.

Benefits

Applications

Tixophalte Wet was developed for sealing leaks and making repairs, also on wet surfaces. Adhesion to all types of roofing felts, including APP- and SBS-modified membranes. For waterproof finishing of overlaps, connections and joints of roof edges, chimneys, light domes and bushings for exhaust pipes. Fixing rain water drain systems onto the roof. Connection of damp courses and other waterproofing wall details (e.g. inner-walls). Fixing overlaps of roofing felt at rising outer walls.

Directions Of Use

Additional information

Application temperature		+5°C to +25°C
Base		Bitumen
Consistency		Paste
Density		1,30 g/ml
Frost resistance during transportation		Up to -15°C
Skin formation	@ +23°C/50% RH	2 hours
Temperature resistance		>90°C

These are typical values

Limitations

· Not suitable for PE, PP, PC, PMMA and PTFE

Surface Preparations and Finishing

Application temperature +5°C to +25°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Substrates to be free of dust and loose particles. Non-porous substrates do not need to be absolutely dry. Always test adhesion prior to application.

Cleaning

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

Colour(s)

Black

Packaging

Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

Store between +5°C and +25°C and in shaded conditions. Shelf life is up to 12 months when stored as recommended in original unopened packaging.







Technical Data Sheet

Shell Tixophalte Wet

Bituminous adhesive and sealant

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any croumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.