

Technical Data Sheet

SX Glue Screws Solvent Free Glue Screws
Bonds wood, plastic, brick and plaster



Product Description

A ready to use, solvent free construction adhesive, based on acrylic polymers, which adheres to most common building surfaces and replaces nails and screws. The adhesive cures by moisture to form a strong and durable bond. Can even be used on damp surfaces with the use of a primer.

Benefits

- Solvent free
- Perfect adhesion without primer on most substrates
- Easy to apply
- Easy to clean
- Non corrosive towards metal

Applications

Can be used indoor to fix skirting boards in both wood and PVCu, thresholds, panels and ornamental framework on to various substrates such as masonry, concrete, plaster, chipboard, plasterboard and wood. Also suitable for the adhesion of polystyrene foam and polystyrene tiles.

Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a sealant gun, apply the adhesive to one surface in a strip form. Position the object into place and apply pressure. On large objects you may need to move the item slightly

from side to side, applying pressure simultaneously, to achieve an effective and even bond. Finally, slide the item into the exact position required. Temporary fixing or clamping may be necessary on unsupported items. Allow 24-72 hours depending on temperature and porosity of the surface before removing any support. Full bonding is usually achieved in 48 - 72 hours.

Additional information

Application rate	@ Ø3 mm/4 bar	1500 g/min
Application temperature		+5°C to +40°C
Base		Acrylic dispersion
Curing time	@ +23°C/50% RH	3 days
Density	ISO 1183-1	1,61 g/ml
Flow	ISO 7390	< 2 mm
Frost resistance during transportation		Up to -15°C
Open time	DBTM 16	5-10 minutes @ +23°C/50% RH
Temperature resistance		-20°C to +75°C
Usage		400-1000g/m2

These are typical values

Limitations

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for continuous exposure to water

Surface Preparations and Finishing

Surfaces must be clean, dry and free from dust, grease and other loose material. At least one of the surfaces has to be porous in order for the adhesive to cure. Adhesion tests prior to application are recommended. Tools should be wiped clean with a paper towel and can be washed in water whilst the adhesive is still uncured.

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap.
Issue14/29.04.16/0094.10.DB

Technical Data Sheet

SX Glue Screws Solvent Free Glue Screws
Bonds wood, plastic, brick and plaster

Colour(s)

- Colourless

Packaging


- Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

In unopened original packaging between +5°C and +25°C, shelf life till 18 months after production date, stored in a dry place.

Certifications

	A+ French VOC Regulation
--	--------------------------

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request and via the Siroflex website on the product pages.

Warranty & Guarantee

Siroflex warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Siroflex Limited. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Siroflex Ltd's written consent. The technical information in this document serves as an indication and is non-exhaustive. Siroflex Ltd is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Siroflex Ltd reserves the right to amend the wording of this document. Siroflex Ltd cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our Terms & Conditions of sale.