

Technical Data Sheet

SX Contractors PU Foam Applicator Gun PU Foam Applicator Gun



Product Description

Contractors PU Foam Applicator Gun

Benefits

Applications

Directions Of Use

Screw the thread of the can onto the valve of the gun until the can is tight, being careful not to strip the threads. Use the plastic adaptor provided to protect the extrusion nozzle during application. Pull the trigger to start the flow of the foam. Regulate the stream of flow by adjusting the rear knob. At the end of the job, screw the regulation knob to lock the needle. This will avoid foam leakage from the nozzle. Before replacing cans, close the gun valve and unscrew empty can. Immediately replace with a full can or clean gun thoroughly with SX PU Foam Cleaner.

Limitations

Surface Preparations and Finishing

Cleaning

Do not remove part used cans from the gun. Keep the canister attached at all times as this will prevent the foam curing within the gun. The foam canister should not be removed until it is empty. Always make sure that the Gun Grade Foam can is totally empty by keeping your finger on the trigger to let out all the gas. To clean the gun, remove the empty Gun Grade Foam can, clean the valve using SX PU Foam Cleaner. Immediately place the can of SX PU Foam Cleaner onto the gun, press the trigger down for at least five seconds, making sure that the solvent travels through the gun to the tip and totally cleans the gun. It is important that the foam is removed from the tip of the extrusion nozzle, as any cured material here will cause a problem later. If after cleaning you find that there is some cured foam at the end of the nozzle or round the ball bearing in the valve, remove this with a pin and use the SX PU Foam Cleaner again, to

ensure that the gun is totally clean and operational. Never leave the foam gun applicator separated from a can of foam without immediately cleaning the gun thoroughly or replacing with a new can of foam. Guns should only be stored when thoroughly cleaned.

Issue1/29.04.16

Colour(s)

- Aluminium

Packaging

- N/A

For product specifications, please refer to the Product Detail Page

Shelf Life

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request and via the Siroflex website on the product pages.

Warranty & Guarantee

Siroflex warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Siroflex Limited. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Siroflex Ltd's written consent. The technical information in this document serves as an indication and is non-exhaustive. Siroflex Ltd is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Siroflex Ltd reserves the right to amend the wording of this document. Siroflex Ltd cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our Terms & Conditions of sale.