

Technical Data Sheet

SX Premium Painters Caulk-it 380 ml Flexible sealant to give a professional finish



Product Description

A premium grade, flexible sealant that is easy to apply, dries quickly and can be over painted with most water based and synthetic paints. For interior and exterior* use. Adheres without primer to most substrates. It is almost odour free and is not corrosive towards metals.

Benefits

- Paintable with water based and synthetic paints
- Perfect adhesion without primer to most substrates
- Interior and exterior use
- Nearly odourless
- Easy to apply
- Easy to clean
- Non corrosive towards metals

Applications

For the sealing and filling of gaps and cracks where movement can occur, such as those between plasterwork, perimeter sealing of window and door frames, skirting boards and architraves. Use prior to painting or wall papering to fill cracks to give a professional finish.

Directions Of Use

Cut the cartridge seal and screw on the nozzle which should be cut to your required size. Using a skeleton gun, apply the sealant into the gap or joint ensuring a good solid fill. If required, place masking tape

along edges, removing within 5 minutes of application. Smooth off whilst wet, do not attempt to abrade when cured.

Additional information

100 % modulus		0.3 N/mm ²
Application rate	@ ø3 mm/4 bar	450 g/min
Application temperature		+5°C to +40°C
Base		Acrylic dispersion
Curing time		5 minutes @23°C /50% RH
Elongation at break		200%
Flow		< 2mm
Frost resistance during transportation		Till -15°C
Joint movement		12.5%
Shorea hardness		30
Temperature resistance		-20°C to +75°C
Tensile strength		0.3 N/mm ²

These are typical values

Limitations

- Not suitable for continuous exposure to water
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

Surface Preparations and Finishing

Surfaces must be clean and solid. Adhesion tests prior to application are recommended. Always tool using a spatula or stick wetted with water within 5 minutes of application. Uncured sealant can be removed with water.

Paintability

Can be over painted with most water based and synthetic paints when sealant is fully cured. Painting over with highly filled water based paints can cause cracks in the paint film. We recommend a paint compatibility test before application.



Technical Data Sheet

SX Premium Painters Caulk-it 380 ml Flexible sealant to give a professional finish

Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with SX Multi-Purpose Cleaning Wipes and/or water and soap. Issue 13/18.03.20/0254.7.BB 310ml Issue 4 /02.03.20/0393.0.BS 380ml Issue3/29.04.16/0306.2.HO 400ml

Colour(s)

- White

Packaging


- Cartridge

For product specifications, please refer to the Product Detail Page

Shelf Life

18 months from the date of manufacture when stored in the dry between +5°C & +25°C, out of direct sunlight. Protect from frost.

Certifications

	EN 15651-1: F-EXT-INT 12.5P
---	-----------------------------

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request and via the Siroflex website on the product pages.

Warranty & Guarantee

Siroflex warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Siroflex Limited. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Siroflex Ltd's written consent. The technical information in this document serves as an indication and is non-exhaustive. Siroflex Ltd is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Siroflex Ltd reserves the right to amend the wording of this document. Siroflex Ltd cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our Terms & Conditions of sale.